ᠵᡘᡀᠻᠹᢪᡭ᠍ᢆᢒᡈᡱᢛᡗᡷᡎ





1. Chemical Product And Company Identification:

Product Name: Toluene

Synonym: Toluol, Tolu-Sol; Methylbenzene; Methacide; Phenyl methane; Methylbenzol

Chemical Name: Toluene

Chemical Formula: C6-H5-CH3 or C7-H8

Company Identification: Iran-Tabriz petrochemical company

2. Composition, Information On Ingredients:

Name: Toluene, CAS No: 108-88-3, Min 98 %Wt

Toxicological Data on Ingredients: Toluene: ORAL (LD50): Acute: 636 mg/kg [Rat].

DERMAL (LD50): Acute 14100 mg/kg

[Rabbit]. VAPOR (LC50): Acute: 49000 mg/m 4 hours [Rat]. 440 ppm 24 hours [Mouse].

3. Hazards Identification:

Potential Acute Health Effects:

Hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact.

Potential Chronic Health Effects:

Carcinogenic effects: A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC.

Mutagenic effects: Not available.

Teratogenic effects: Not available.

Developmental toxicity: Not available. The substance may be toxic to blood, kidneys, the nervous system, liver, brain, central nervous system (CNS).

Repeated or prolonged exposure to the substance can produce target organs damage.

4. First Aid Measures:

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin Contact:

In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.





ᡊᡭᠯᢔᡋᠹᠯᢗᢆᡭᢆᠦᡱᢛᢓᡲᡎ



TPC) it District to the second secon	MSDS	ISSUE DATE	Juene-2020
		WWW.TPCO.IR	
	TOLUENE GRADE I	IRAN/TABRIZ/TABRIZ PETROCHEMICAL COMPANY/P.O.BOX:51745-354/TEL:+984134282612	
to you		P	age:2/7

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention.

Ingestion:

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband. Serious Ingestion: Not available.

5. Fire Fighting Measures:

Flammability of the Product: Flammable. Auto-Ignition Temperature: 480°C (896°F)

Flash Points: CLOSED CUP: 4.4444°C (40°F). (Seta flash) OPEN CUP: 16°C (60.8°F).

Flammable Limits: LOWER: 1.1% UPPER: 7.1%

Products of Combustion: These products are carbon oxides and carbon monoxide (CO, CO2).

Fire Hazards in Presence of Various Substances:

Flammable in presence of open flames and sparks, of heat. Non-flammable in presence of shocks.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Flammable liquid, insoluble in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray or fog.

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards:

Toluene forms explosive reaction with 1, 3-dichloro-5, 5-dimethyl-2, 4-imidazolididione; di nitrogen tetra oxide; concentrated nitric acid, sulfuric acid + nitric acid; N2O4; AgClO4; BrF3; Uranium hexafluoride; sulfur dichloride. Also forms an explosive mixture with tetra nitro methane.





ᠵᡘᡀᠻᠹᢪᡭ᠍ᢆᢒᡈᢡᡊᡲᡎ



TPC in the special spe	MSDS	ISSUE DATE	Juene-2020
		WWW.TPCO.IR	
	TOLUENE GRADE I	IRAN/TABRIZ/TABRIZ PETROCHEMICAL COMPANY/P.O.BOX:51745-354/TEL:+984134282612	
SAME!		Pi	age:3/7

6. Accidental Release Measures:

Small Spill: Absorb with an inert material and put the spilled material in an appropriate waste disposal.

Large Spill:

Toxic flammable liquid, insoluble or very slightly soluble in water. Keep away from heat. Keep away from sources of ignition.

Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container.

Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

7. Handling And Storage:

Precautions:

Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.

Storage:

Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

8. Exposure Controls, Personal Protection:

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection:

Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:





ᡊᡭᠯᢔᡋᠻᠯᡭᠯᢗᡈᡱᢛᡶᢅᡎ



TPC in the control of the control o	MSDS	ISSUE DATE	Juene-2020
		WWW.TPCO.IR	
	TOLUENE GRADE I	IRAN/TABRIZ/TABRIZ PETROCHEMICAL COMPANY/P.O.BOX:51745-354/TEL:+984134282612	
	TOLOUNE ON TOLOU	P	age:4/7

TWA: 100 STEL: 500 CEIL: 150 (ppm) from OSHA (PEL) [United States] TWA: 20 (ppm)

from ACGIH (TLV) [United States]

SKIN TWA: 100 STEL: 150 from NIOSH [United States] TWA: 375 STEL: 560 (mg/m3)

from NIOSH [United States] Consult local authorities for acceptable exposure limits.

9. Physical And Chemical Properties:

Physical state and appearance: Liquid. Odor: Sweet, pungent, Benzene-like.

Taste: Not available.

Molecular Weight: 92.14 g/mole

Color: Colorless

PH (1% sol/water): Not applicable. Boiling Point: 110.6°C (231.1°F) Melting Point: -95°C (-139°F)

Critical Temperature: 318.6°C (605.5°F)

Specific Gravity: 0.8636 (Water = 1)

Vapor Pressure: 3.8 kPa (@ 25°C)

Vapor Density: 3.1 (Air = 1)

Volatility: Not available. Odor Threshold: 1.6 ppm

Water/Oil Dist. Coeff: The product is more soluble in oil; log (oil/water) = 2.7

Dispersion Properties: See solubility in water, diethyl ether, and acetone.

Solubility:

Soluble in diethyl ether, acetone. Practically insoluble in cold water. Soluble in ethanol, benzene, chloroform, glacial acetic acid, carbon disulfide. Solubility in water: 0.561 g/l @ 25 deg. C.

10. Stability And Reactivity:

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Heat, ignition sources (flames, sparks, static), incompatible materials

Incompatibility with various substances: Reactive with oxidizing agents.

Corrosion: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Incompatible with strong oxidizers, silver perchlorate, sodium difluoride, Tetranitromethane, Uranium Hexafluoride. Frozen Bromine Trifluoride reacts violently with Toluene at -80 deg. C. Reacts chemically with nitrogen oxides, or halogens to form nitro toluene, nitrobenzene, and nitro phenol and halogenated products, respectively.

Special Remarks on Corrosion: Not available.

Polymerization: Will not occur.





ᡊᡭᠯᢔᡐᠹᢪᡭ᠍ᢆᢒᡈᢡᢨᢋ



TPC	MSDS	ISSUE DATE	Juene-2020
		WWW.TPCO.IR	
	TOLUENE GRADE I	IRAN/TABRIZ/TABRIZ PETROCHEMICAL COMPANY/P.O.BOX:51745-354/TEL:+984134282612 Page:5/7	

11. Toxicological Information:

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion. Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 636 mg/kg [Rat]. Acute dermal toxicity (LD50): 14100 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 440 (at 24 hours) [Mouse]. Chronic Effects on Humans:

CARCINOGENIC EFFECTS: A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC.

May cause damage to the following organs: blood, kidneys, the nervous system, liver, brain, central nervous system (CNS).

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact.

Special Remarks on Toxicity to Animals:

OWEST Published Lethal Dose: LDL [Human] - Route: Oral; Dose: 50 mg/kg LCL [Rabbit] - Route: Inhalation; Dose: 55000 ppm/40min

Special Remarks on Chronic Effects on Humans:

Detected in maternal milk in human. Passes through the placental barrier in human.

May cause adverse reproductive effects and birth defects (teratogenic). May affect genetic material (mutagenic)

Special Remarks on other Toxic Effects on Humans: Acute Potential Health Effects: Skin: Causes mild to moderate skin irritation. It can be absorbed to some extent through the skin. Eyes: Causes mild to moderate eye irritation with a burning sensation. Splash contact with eyes also causes conjunctivitis, corneal edema, and corneal abrasions. This usually resolves in 2 days. Inhalation: Inhalation of vapor may cause respiratory tract irritation causing coughing and wheezing, and nasal discharge. Inhalation of high concentrations may affect behavior and cause central nervous system effects characterized by nausea, headache, dizziness, tremors, restlessness, lightheadedness, exhilaration, memory loss, insomnia, impaired reaction time, drowsiness. ataxia. hallucinations, somnolence, muscle contraction spasticity. unconsciousness and coma. Inhalation of high concentration of vapor may also affect the cardiovascular system (rapid heartbeat, heart palpitations, increased or decreased blood pressure, respiration, acute pulmonary edema, respiratory depression, apnea, and asphyxia), cause vision disturbances and dilated pupils, and cause loss of appetite.

Ingestion:

Aspiration hazard: Aspiration of Toluene into the lungs may cause chemical pneumonitis. May cause irritation of the digestive tract with nausea, vomiting, pain. May have effects similar to that of acute inhalation.

Chronic Potential Health Effects:

*භී*වුර් ඉඩ්රී වියු දෙදිම



TPC in the property of the pr	MSDS	ISSUE DATE	Juene-2020
		WWW.TPCO.IR	
	TOLUENE GRADE I	IRAN/TABRIZ/TABRIZ PETROCHEMICAL COMPANY/P.O.BOX:51745-354/TEL:+984134282612	
		Pi	age:6//

Inhalation and Ingestion: Prolonged or repeated exposure via inhalation may cause central nervous system and cardiovascular symptoms similar to that of acute inhalation and ingestion as well liver damage/failure, kidney damage/failure, brain damage, weight loss, blood (pigmented or nucleated red blood cells, changes in white blood cell count), bone marrow changes, electrolyte imbalances.

Skin: Repeated or prolonged skin contact may cause dermatitis.

12. Ecological Information:

Ecotoxicity:

Ecotoxicity in water (LC50): 313 mg/l 48 hours [Daphnia (daphnia)]. 17 mg/l 24 hours [Fish (Blue Gill)]. 13 mg/l 96 hours [Fish (Blue Gill)]. 56 mg/l 24 hours [Fish (Fathead minnow)]. 34 mg/l 96 hours [Fish (Fathead minnow)]. 56.8 ppm any hours [Fish (Goldfish)].

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

13. Disposal Considerations:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

14. Transport Information:

DOT Classification: CLASS 3: Flammable liquid.

Identification: Toluene UNNA: 1294 PG: II Special Provisions for Transport: Not available.



ᡊᡭᠯᢔ᠍ᠹᠹᢪᡭᢗᡈᡱᢅᢛᡓᡲᡎ



TPC)	MSDS	ISSUE DATE	Juene-2020
		WWW.TPCO.IR	
	TOLUENE GRADE I	IRAN/TABRIZ/TABRIZ PETROCHEMICAL COMPANY/P.O.BOX:51745-354/TEL:+984134282612	
10,000		Pa	age:7/7

15. Regulatory Information:

NFPA Ratings (Scale 0-4): Health=2 Fire=3 Reactivity=0

Protective Equipment:

Gloves. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

16. Other Information:

References: Not available.

Other Special Considerations: Not available.

Although the information contained in this document is presented in good faith, base on available information believed to be reliable at the time of preparation of this document, TPC makes no warranties or representations with respect to the information or the products described herein, and expressly disclaims all implied warranties and conditions (including all warranties and conditions of merchantability or fitness for a particular purpose).this information is subject to change without notice. Responsibility for use, storage, handling and disposal of the products described herein, whether alone or in combination with any other substance, is that of the purchaser and/or end user.